

Touch PoS Systems

E-Touch Jade 365



The E-Touch Jade 365 series is an innovative “Fanless” design that operates at low noise, low power consumption and minimal maintenance. Tool-less modular construction is easy to maintain and service, and therefore significantly reduces total cost of ownership. Its small footprint and VESA wall-mountable features are ideal for applications where space is at a premium

Advantages

- Low power consumption and fanless for quiet operation
- Easy access mechanical design for HDD and Compact Flash maintenance and upgrades
- Optional peripherals such as MSR, Programmable Keypad, Customer Display and 2nd Display are available for challenging operating environments
- All-in-one MB design for I/O card and cable material cost reduction

Features

- Small footprint 280 (W) x 250 (D)
- Easy HDD & Motherboard access
- VESA wall-mountable
- Magnetic Strip Card Reader
- Programmable Keypad (32 keys) / Magnetic Strip Card Reader / Smart IC Card Reader
- Second Display (7”, 8.4”, 10”, 12.1” TFT LCD) or Customer Display (VFD or LCD)

Applications

- Supermarket
- Merchant Establishments
- Pharmacy
- Malls
- Restaurants
- Hospitals

Specifications

Model Name	Jade 362	Jade 365
Mainboard	B78	
CPU Supports	Celeron M ULV 1GHz	
Chipset	Intel 852GM FSB 400 MHz / ICH4	
System Memory	1 x DDR SO-DIMM Slot Up to 1GB	
Graphic Memory	System Memory Shared Up to 64MB	
LCD Panel		
LCD Size	12.1" TFT	15" TFT
Brightness	150 - 400 cd / m ²	250 cd / m ²
Maximal Resolution	800 x 600 / 1024 x 768	1024 x 768
Touch Screen Type	Resistive	
Tilt Angle (Degree)	-25° ~ 65°	
Storage		
HDD	1 x 2.5" slim HDD bay or 3.5" HDD bay	
Flash Memory	Compact Flash Memory Option (Type I & II)	
Expansion		
Mini-PCI Socket	1 x Mini-PCI	
External I/O		
USB 2.0	4 x USB Type A	
Serial / COM	4 x COM ports RJ-45 connectors (COM1 & COM2 standard RS-232; COM3 & COM4 pin 9 with 5V or 12V power by jumper)	
Parallel	1 x DB 25F	
LAN (10 / 100)	1 x RJ45	
2nd VGA	1 x DB 15F	
Cash Drawer	1 x RJ-11 (12V / 19V)	
Audio	1 x Line-in / 1 x Line-out	
Control / Indicator		
Power Button	1	
LED Indicator	1	
Power		
Power Adaptor	External 90W AC	
Peripheral		
Customer Display	VFD / LCD Pole Display	
Second Display	7" / 8.4" / 10" / 12.1" TFT LCD	
Magnetic Card Reader	3 Tracks (RS-232 / PS2 interface)	
Programmable Keypad / Card Reader	32 keys with key lock / Magnetic Card Reader (PS2 Interface) / Smart IC Card Reader (USB Interface)	
Environment		
EMC & Safety	FCC Class A / CE Marking / LVD	
Operating Temperature	5 ~ 35°C (41°F ~ 95°F)	
Storage Temperature	-20°C ~ 55°C (-4°F ~ 131°F)	
Operating Humidity	20% - 85% RH non-condensing	
Storage Humidity	20% - 85% RH non-condensing	
Dimension (W x H x D)	POS 362: 308 x 265 x 325 mm / 12.1" x 10.4" x 12.8" POS 365: 385 x 265 x 384 mm / 15.2" x 10.1" x 15.1"	
OS Support	Windows XP, WEPOS, XP Embedded, XP Professional for Embedded, Win 2000 Professional Embedded, WIN NT 4.0, Linux, Red Hat 7.2	

E-PoS International LLC

P.O. Box : 44960 Dubai, U.A.E.

Tel. : +971 4 3523288, 3512861

Fax : +971 4 3513396

E-mail : sales@eposintl.com www.eposintl.com

Our Business Partner